High Definition Digital Signage

75HDK231B 65HDS231B 75HDS231B 75HDT231B





AVIATION TECHNOLOGY INFRASTRUCTURE CORPORATION



75HDK231B



- Origin LG panel: LED backlight provide high brightness uniformity without border shadows
- Wide viewing angle keeping display brightness and contrast
- The screen is anti-violent, scratch-resistant, dust-proof and waterproof that helps you maintain in better, 4mm tempered glass
- 24/7 commercial use of uninterrupted work with the stable performance, automatic switch machine will get an administrator schedule and act exactly based on your set time
- Eco-friendly power timer lets you assign hourly, daily or weekly on and off times for screen
- Application in museums, exhibitions, shopping malls, self-ordering touchscreen kiosk in hotels, restaurants, cafes ...













Education

Schedule

Check-in

Catalogue

Purchase Ticket

Order



Туре	High Definition Full Screen Kiosk Digital Signage
Model	75HDK231B
Display	LG Panel
Panel Size (diagonal)	75 inch
Panel Technology	IPS
Backlight	D-LED
Resolution	3840x2160p (UltraHD)
Visible Area	1650 x 928 mm
Color Support	1.07B (10-bit)
Brightness	500 nits
Contrast Ratio	1200:1
View Angle	178° 178°
Life time	50000 hours
Response Time	8 ms
Refresh Rate	60 Hz
System	
Operating System	Android 11
CPU	RK3568 2.0GHz
RAM / ROM	8GB / 32GB
Connectivity	
Port	USB 2.0, USB 3.0, HDMI 2.0, RJ45, Audio 3.5mm
Network	Wifi 2.4G/5G, Ethernet, Bluetooth
General	
Power Supply	100-240 VAC, 50/60 Hz, 2A
Power Consumption	< 170W
Dimension	1768 x 996.34 x 118.5 mm
Speaker	2x3W
Operating Temperature	0°C ~ 40°C
Operating Humidity	20% ~ 80% (non-condensing)
Language	English
Accessories	Power cable, Floor stand, Wheel, Remote



65HDS231B



- Origin LG panel: long durability, positive power tolerance, reliable for the future, 24/7 operation
- High contrast and high brightness effectively sharp image and true color
- Strong impact resistant with tempered glass
- 4K resolution supports high-quality image projection
- Surround sound support with 2x8W power
- Diverse connectivity: Wifi, Bluetooth, LAN, USB
- Latest Android OS: support for installing popular media apps
- Metal case protects the units from interference of radiation, magnetic fields and strong electiric fields
- Energy saving and environmental protectionpular media apps











Туре	High Definition Digital Signage
Model	65HDS231B
Display	LG Panel
Panel Size (diagonal)	65"
Panel Technology	IPS
Backlight	D-LED
Resolution	3840x2160p (UltraHD)
Color Support	1.07B (10-bit)
Brightness	500 nits
Aspect Ratio	16:9
Fresh Rate	60Hz
Response Time	8 ms
Contrast Ratio	1200:1
Life time	50000 hours
View Angle	178° 178°
Orientation	Landscape / Portrait
System	
Operating System	Android 11
CPU	RK3568
RAM / ROM	8GB / 32GB
Connectivity	
Port	1*HDMI 2.0, 2*USB, 1*RJ45, 1*Audio 3.5mm
Network	Wifi 5G, Ethernet, Bluetooth
General	
Power Supply	100-240 VAC, 50/60 Hz
Power Consumption	< 115W
Dimension / Weight	1469 x 845 x 69 mm / 33Kg
Operating Temperature	0°C ~ 40°C
Operating Humidity	20% ~ 80% (non-condensing)
Material	Fully sprayed hardware back panel
Language	English
Accessoriess	Wall mount, Remote control, Wifi antenna, Power cord
Certificate	CE / FCC / RoHS / ISO 9001





75HDS231B





•

- Origin LG panel: long durability, positive power tolerance, reliable for the future, 24/7 operation
- ر ا
- future, 24/7 operationHigh contrast and high brightness effectively sharp image and true color
- Strong impact resistant with tempered glass
- 4K resolution supports high-quality image projection
- Surround sound support with 2x8W power
- Diverse connectivity: Wifi, Bluetooth, LAN, USB
- Latest Android OS: support for installing popular media apps



- Metal case protects the units from interference of radiation, magnetic fields and strong electric fields
- Energy saving and environmental protection media apps



Туре	High Definition Digital Signage
Model	75HDS231B
Display	LG Panel
Panel Size (diagonal)	75″
Panel Technology	IPS
Backlight	D-LED
Resolution	3840x2160p (UltraHD)
Color Support	1.07B (10-bit)
Brightness	500 nits
Aspect Ratio	16:9
Fresh Rate	60Hz
Response Time	8 ms
Contrast Ratio	1200:1
Life time	50000 hours
View Angle	178° 178°
Orientation	Landscape / Portrait
System	
Operating System	Android 11
CPU	RK3568
RAM / ROM	8GB / 32GB
Connectivity	
Port	1*HDMI 2.0, 2*USB, 1*RJ45, 1*Audio 3.5mm
Network	Wifi 5G, Ethernet, Bluetooth
General	
Power Supply	100-240 VAC, 50/60 Hz
Power Consumption	< 190W
Dimension / Weight	1768 x 996.34 x 118.5 mm / 64Kg
Operating Temperature	0°C ~ 40°C
Operating Humidity	20% ~ 80% (non-condensing)
Material	Fully sprayed hardware back panel
Language	English
Accessoriess	Wall mount, Remote control, Wifi antenna, Power cord
	Wair mount, Remote control, Will antenna, Power cora





100HDS231B



- Origin LG panel: long durability, positive power tolerance, reliable for the future, 24/7 operation
- High contrast and high brightness effectively sharp image and true color
- Ultra-thin: industrial-grade appearance, the thickness of the whole body is mm111, and the screen printing frame is 35mm
- Explosion-proof: the decorative glass on the surface is 3.5mm high-strength physical tempered glass
- 4K resolution supports high-quality image projection
- Diverse connectivity: Wifi, Bluetooth, LAN, USB
- Latest Android OS: support for installing popular media apps
- Performance: The internal heat dissipation adopts the convection method, no problem long-term load work
- Metal case protects the units from interference of radiation, magnetic fields and strong electiric fields
- Energy saving and environmental protectionpular media apps











ModelIO0HDS231BDisplayLG PanelPanel Size (diagonal)100°Panel TechnologyIPSBacklightD-LEDResolution3840x2160p (UltraHD)Color Support1.078 (10-bit)Brightness500 nitsAspect Ratio60HzViewing Angle128° 178°OrientationLandscape / PortraitSystemOperating SystemAndroid 11CPURK3568RAM / ROM8GB / 64GBConnectivityPort1°HDMI 2.0, 1°LJS 1,*Audio 3.5mmNetwork10°C - 40°COperating Temperature10°C - 40°COperating Temperature20% ~ 80% (non-condensing)FrameAuminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifn antenna, Power	Туре	High Definition Digital Signage
Panel Size (diagonal)100°Panel TechnologyIPSBacklightD-LEDResolution3840x2160p (UltraHD)Color Support1.07B (10-bit)Brighness500 nitsAspect Ratio16:9Fresh Rate60HzViewing Angle178° 178°OrientationLandscape / PortraitSystem700Operating SystemAndroid 11CPURK3568RAM / ROM8GB / 64GBConnectivity700Port1'HDMI 2.0, 1"USB 2.0, 1"RJ45, 1"Audio 3.5mmNetworkWift 5G, Ethernet, BluetoothGeneral100-240 VAC, 50/60 HzPower Supply100-240 VAC, 50/60 HzPower Supply100-240 VAC, 50/60 HzOperating Temperature10°C ~ 40°COperating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageFully sprayed hardware back panelAccessoriessWoll mount, Remote control, Wifi antenna, Power cont	Model	100HDS231B
Panel Technology IPS Backlight D-LED Resolution 3840x2160p (UltraHD) Color Support 1.07B (10-bit) Brightness 500 nits Aspect Ratio 16/9 Fresh Rate 60Hz Viewing Angle 178° 178° Orientation Landscape / Portrait System Color Support Operating System Android 11 CPU RK3568 RAM / ROM 8GB / 64GB Connectivity Yes Port 1'HDMI 2.0, 1"USB 2.0, 1"RJ45, 1"Audio 3.5mm Network Wifi 5G, Ethernet, Bluetooth General Yes Power Consumption <480W Dimension / Weight 1870 x 1140 x 210 mm / 125Kg Operating Temperature 10°C ~ 40°C Operating Temperature 20% ~ 80% (non-condensing) Frame Aluminum profile (oxidized wire drawing) Material Fully sprayed hardware back panel Language English, Simplified Chinese Accessoriess Woll mount, Remote control, Wif	Display	LG Panel
BacklightD-LEDResolution3840x2160p (UltraHD)Color Support1.07B (10-bit)Brightness500 nitsAspect Ratio16:9Fresh Rate60HzViewing Angle178° 178°OrientationLandscape / PortraitSystemColor SupportOperating SystemAndroid 11CPURK3568RAM / ROM8GB / 64GBConnectivityViewing AnglePort1'HDMI 2.0, 1"USB 2.0, 1"RJ45, 1"Audio 3.5mmNetworkWift 5G, Ethernet, BluetoothGeneralViewing AnglePower Supply100-240 VAC, 50/60 HzPower Consumption< 480WDimension / Weight1870 x 1140 x 210 mm / 125KgOperating Temperature10°C ~ 40°COperating Temperature10°C ~ 40°COperating Temperature10°C ~ 40°COperating TemperatureEnglish, Simplified ChineseAluminum profile (oxidized wire drawing)FrameMaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cond	Panel Size (diagonal)	100″
Resolution 3840x2160p (UltraHD) Color Support 1.07B (10-bit) Brightness 500 nits Aspect Ratio 16:9 Fresh Rate 60Hz Viewing Angle 178° 178° Orientation Landscape / Portrait System Operating System Android 11 CPU RK3568 RAM / ROM 8GB / 64GB Connectivity Port 1'HDMI 2.0, 1''USB 2.0, 1''R.J45, 1'Audio 3.5mm Network Wifi 5G, Ethernet, Bluetooth General Power Supply 100-240 VAC, 50/60 Hz Power Consumption 480W 1870 × 1140 × 210 mm / 125Kg Operating Temperature 0°C ~ 40°C Operating Temperature 0°C ~ 40°C Operating Humidity 20% ~ 80% (non-condensing) Frame Hauminum profile (oxidized wire drawing) Material Language English, Simplified Chinese Accessoriess Wall mount, Remote control, Wifi antenna, Power cord	Panel Technology	IPS
Color Support 1.07B (10-bit) Brightness 500 nits Aspect Ratio 16:9 Fresh Rate 60Hz Viewing Angle 178° 178° Orientation Landscape / Portrait System Operating System Android 11 CPU RK3568 RAM / ROM 8GB / 64GB Connectivity Port 1*HDMI 2.0, 1*USB 2.0, 1*RJ45, 1*Audio 3.5mm Network Wift 5G, Ethernet, Bluetooth General Power Consumption <480W	Backlight	D-LED
Brightness 500 nits Aspect Ratio 16:9 Fresh Rate 60Hz Viewing Angle 178° 178° Orientation Landscape / Portrait System Corientation Operating System Android 11 CPU RK3568 RAM / ROM 8GB / 64GB Connectivity Viei 5G, Ethernet, Bluetooth Port 1*HDMI 2.0, 1*USB 2.0, 1*RJ45, 1*Audio 3.5mm Network Wifi 5G, Ethernet, Bluetooth General Viei 5G, Ethernet, Bluetooth Power Supply 100-240 VAC, 50/60 Hz Power Consumption <480W	Resolution	3840x2160p (UltraHD)
Aspect Ratio 16:9 Fresh Rate 60Hz Viewing Angle 178° 178° Orientation Landscape / Portrait System Viewing Angle Operating System Android 11 CPU RK3568 RAM / ROM 8GB / 64GB Connectivity Bog / 64GB Port 1*HDMI 2.0, 1*USB 2.0, 1*RJ45, 1*Audio 3.5mm Network Wifi 5G, Ethernet, Bluetooth General Vieght Power Supply 100-240 VAC, 50/60 Hz Power Consumption < 480W	Color Support	1.07B (10-bit)
Fresh Rate60HzFresh Rate60HzViewing Angle178° 178°OrientationLandscape / PortraitSystemLandscape / PortraitOperating SystemAndroid 11CPURK3568RAM / ROM8GB / 64GBConnectivityVifi 5G, Ethernet, BluetoothPort1*HDMI 2.0, 1*USB 2.0, 1*RJ45, 1*Audio 3.5mmNetworkWifi 5G, Ethernet, BluetoothGeneralVifi 5G, Ethernet, BluetoothPower Supply100-240 VAC, 50/60 HzPower Consumption< 480W	Brightness	500 nits
Viewing Angle178° 178°Viewing AngleLandscape / PortraitOprentationLandscape / PortraitSystemAndroid 11Operating SystemAndroid 11CPURK3568RAM / ROM8GB / 64GBConnectivityYour State S	Aspect Ratio	16:9
OrientationLandscape / PortraitSystemAndroid 11Operating SystemAndroid 11CPURK3568RAM / ROM8GB / 64GBConnectivityPortPort1*HDMI 2.0, 1*USB 2.0, 1*RJ45, 1*Audio 3.5mmNetworkWifi 5G, Ethernet, BluetoothGeneralPower SupplyPower Consumption< 480WDimension / Weight1870 x 1140 x 210 mm / 125KgOperating Temperature10°C ~ 40°COperating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cond	Fresh Rate	60Hz
SystemOperating SystemAndroid 11CPURK3568RAM / ROM8GB / 64GBConnectivityPort1*HDMI 2.0, 1*USB 2.0, 1*RJ45, 1*Audio 3.5mmNetworkWifi 5G, Ethernet, BluetoothGeneralPower Supply100-240 VAC, 50/60 HzPower Consumption< 480WDimension / Weight1870 x 1140 x 210 mm / 125KgOperating Temperature10°C ~ 40°COperating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	Viewing Angle	178° 178°
Operating SystemAndroid 11CPURK3568RAM / ROM8GB / 64GBConnectivityPort1*HDMI 2.0, 1*USB 2.0, 1*RJ45, 1*Audio 3.5mmNetworkWifi 5G, Ethernet, BluetoothGeneralPower Supply100-240 VAC, 50/60 HzPower Consumption< 480WDimension / Weight1870 x 1140 x 210 mm / 125KgOperating Temperature10°C ~ 40°COperating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	Orientation	Landscape / Portrait
CPURK3568RAM / ROM8GB / 64GBConnectivityPort1*HDMI 2.0, 1*USB 2.0, 1*RJ45, 1*Audio 3.5mmNetworkWifi 5G, Ethernet, BluetoothGeneralPower Supply100-240 VAC, 50/60 HzPower Consumption< 480WDimension / Weight1870 x 1140 x 210 mm / 125KgOperating Temperature10°C ~ 40°COperating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	System	
RAM / ROM8GB / 64GBConnectivityPort1*HDMI 2.0, 1*USB 2.0, 1*RJ45, 1*Audio 3.5mmNetworkWifi 5G, Ethernet, BluetoothGeneral100-240 VAC, 50/60 HzPower Supply100-240 VAC, 50/60 HzPower Consumption< 480WDimension / Weight1870 x 1140 x 210 mm / 125KgOperating Temperature10°C ~ 40°COperating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	Operating System	Android 11
ConnectivityPort1*HDMI 2.0, 1*USB 2.0, 1*RJ45, 1*Audio 3.5mmNetworkWifi 5G, Ethernet, BluetoothGeneralPower Supply100-240 VAC, 50/60 HzPower Consumption< 480W	CPU	RK3568
Port1*HDMI 2.0, 1*USB 2.0, 1*RJ45, 1*Audio 3.5mmNetworkWifi 5G, Ethernet, BluetoothGeneralPower Supply100-240 VAC, 50/60 HzPower Consumption< 480WDimension / Weight1870 x 1140 x 210 mm / 125KgOperating Temperature10°C ~ 40°COperating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialEully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	RAM / ROM	8GB / 64GB
NetworkWifi 5G, Ethernet, BluetoothGeneralPower Supply100-240 VAC, 50/60 HzPower Consumption< 480WDimension / Weight1870 x 1140 x 210 mm / 125KgOperating Temperature10°C ~ 40°COperating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	Connectivity	
GeneralPower Supply100-240 VAC, 50/60 HzPower Consumption< 480WDimension / Weight1870 x 1140 x 210 mm / 125KgOperating Temperature10°C ~ 40°COperating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	Port	1*HDMI 2.0, 1*USB 2.0, 1*RJ45, 1*Audio 3.5mm
Power Supply100-240 VAC, 50/60 HzPower Consumption< 480WDimension / Weight1870 x 1140 x 210 mm / 125KgOperating Temperature10°C ~ 40°COperating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	Network	Wifi 5G, Ethernet, Bluetooth
Power Consumption< 480WDimension / Weight1870 x 1140 x 210 mm / 125KgOperating Temperature10°C ~ 40°COperating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	General	
Dimension / Weight1870 x 1140 x 210 mm / 125KgOperating Temperature10°C ~ 40°COperating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	Power Supply	100-240 VAC, 50/60 Hz
Operating Temperature10°C ~ 40°COperating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	Power Consumption	< 480W
Operating Humidity20% ~ 80% (non-condensing)FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	Dimension / Weight	1870 x 1140 x 210 mm / 125Kg
FrameAluminum profile (oxidized wire drawing)MaterialFully sprayed hardware back panelLanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	Operating Temperature	10°C ~ 40°C
Material Fully sprayed hardware back panel Language English, Simplified Chinese Accessoriess Wall mount, Remote control, Wifi antenna, Power cord	Operating Humidity	20% ~ 80% (non-condensing)
LanguageEnglish, Simplified ChineseAccessoriessWall mount, Remote control, Wifi antenna, Power cord	Frame	Aluminum profile (oxidized wire drawing)
Accessoriess Wall mount, Remote control, Wifi antenna, Power cord	Material	Fully sprayed hardware back panel
	Language	English, Simplified Chinese
Certificate CE / FCC / RoHS / ISO 9001	Accessoriess	Wall mount, Remote control, Wifi antenna, Power cord
	Certificate	CE / FCC / RoHS / ISO 9001



024 3999 1186 09 8822 6669

inspired@aicorp.tech www.aicorp.tech

